

NOTABLE FEATURES



3-Point Serviceability:

Designed with improved serviceability in mind. Access points on console panel, front panel and toe panel simplify maintenance.



Inverter-Driven Motor:

Intelligent inverter measures performance, monitors motor limits and effectively balances load to ensure maximum water extraction during final spin.



Soft Mount:

Rugged and ready to perform with SUSPA® shocks and industrial-grade springs that deliver high-spin speeds, up to 450G, and don't require bolt down.



Ergonomic Door Handle:

Rugged Easy Lock handle design boosts machine durability and provides a secure close.

ECOWASH COMMERCIAL WASHERS



Engineered with intelligence. Designed for versatility. Built to industrial-grade standards. All to deliver durable performance beyond the everyday.

EWH SOFT-MOUNT 450-G OPL WASHER

HIGH-SPIN BASIC OPL MODEL NUMBERS

EWH-25M2 EWH-30M2
EWH-40M2 EWH-60M2

ADVANCED OPL MODEL NUMBERS

EWH-25MP2 EWH-30MP2
EWH-40MP2 EWH-60MP2



Shown with MP2 Controller



See ADClaudry.com for full warranty details.

ADDITIONAL FEATURES

- **Full Stainless Steel Cabinet:** Protects against corrosion and enhances machine's longevity.
- **7 External Chemical Injection Ports:** M2 Controller/4 signals, MP2 Controller/7 signals accurately dispense precise mix of chemicals at optimal time throughout the wash cycle.
- **Hinged Control Panel:** Hinged, front-panel design allows convenient, easy access to internal components eliminating the need to remove the entire console when servicing.
- **Flexible Water Level Settings:** Helps to maximize water savings and customizes wash cycles for varied applications.

A pioneering history and a prolific future. ADC, a Whirlpool Corporation brand, creates innovative, performance-built equipment to handle the trials of daily commercial laundry use. Our reliable machines continue to prove why our name has a reputation for steadfast, innovative and versatile solutions the industry counts on.

	EWH-25M2 EWH-25MP2	EWH-30M2 EWH-30MP2	EWH-40M2 EWH-40MP2	EWH-60M2 EWH-60MP2
DRUM				
Load Capacity (lb/kg)	25 / 10	30 / 13	40 / 18	60 / 25
Drum Volume (cu. ft./liter)	3.3 / 94	4.60 / 130	6.4 / 181	8.7 / 247
Drum Diameter (in/mm)	21 / 533	24 ¾ / 620	27 ½ / 700	30 ¾ / 770
Drum Depth (in/mm)	16 ¾ / 425	16 ¾ / 430	18 ½ / 470	20 ¾ / 530
DIMENSIONS				
Width (in/mm)	27 ¼ / 692	31 / 788	34 ¾ / 883	38 ½ / 979
Depth (cabinet) (in/mm)	31 ½ / 791	31 ½ / 800	33 ¼ / 845	38 ¼ / 973
Depth (overall) (in/mm)	32 ¾ / 832	34 ½ / 867	36 / 914	41 / 1041
Height (in/mm)	45 ¾ / 1162	51 ¾ / 1310	55 ¾ / 1414	61 ½ / 1553
Weight (lb/kg)	467 / 212	560 / 254	767 / 348	1107 / 502
DIMENSIONS WITH PACKAGING				
Crated Width (in/mm)	29 ½ / 749	33 ¾ / 857	37 ¾	41 ¾
Crated Depth (in/mm)	39 ¼ / 997	39 ¼ / 997	41 ¼	46 ½
Crated Height (in/mm)	56 / 1422	61 ¾ / 1568	67	71 ¼
Crated Weight (lb/kg)	528 / 240	634 / 288	849 / 386	1206 / 548
DOOR				
Height to Bottom of Door	16 ¾ / 421	17 / 432	18 ¾ / 479	23 ¾ / 595
Door Opening Diameter (in/mm)	11 ¾ / 290	14 ¾ / 373	14 ¾ / 373	14 ¾ / 373
POWER				
Voltage / Phase (50hz or 60hz)	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH
Full Load Current / Breaker (amps)—1PH	3.5/15	6.8/15	10.1/15	13.7/20
Full Load Current / Breaker (amps)—3PH	3.5/15	6.8/15	10.1/15	7.5/15
CONNECTIONS				
Water Inlet (GHT/BSP)	¾" / ¾"	¾" / ¾"	¾" / ¾"	¾" / ¾"
Steam Inlet (BSP)	½"	½"	½"	¾"
Drain (in/mm)	3 / 76	3 / 76	3 / 76	3 / 76
CYLINDER SPEED				
Washing Speed (rpm)	50	50	47	45
Spinning Speed (rpm)	1245	1150	1080	900
G-Force	450	450	450	350
WATER				
Average Usage (gallons)*	25	29	36.8	42.5

*One wash, two rinse cycles. No wash load.

Intuitive Micro Controls (IMC)

The M2 Controller comes standard on ADC machines and provides a wide variety of programmable controls and cycle options. The optional MP2 Controller upgrade offers even greater customizability and control over your machine's cycles and capabilities.

M2 Controller (Standard)



- 10 cycle options
- Selectable water levels
- Selectable wash temperatures
- Modify cycle times in wash, rinse and spin phase
- Rapid cycle advance
- Simple diagnostic control

MP2 Controller (Optional Upgrade)



- 99 cycle options
- 16 standard cycles
- 83 programmable cycles
- Fully programmable cycles with computer software-enabled setup capabilities
- Rapid cycle advance
- Simple diagnostic control