

ADC EWR 200G OPL Washer



Shown with MP Controller

Features

- Rigid-Mount/200 G-Force
- M Controller with 10 Programmable Cycle Options
- Optional MP Controller with 99 Programmable Cycle Options/ 16 Fixed Cycles
- Inverter-Driven Motor
- Intuitive Micro Controls (IMC)
- Load Unbalance Detection
- Full Stainless-Steel Cabinet
- 7 External Chemical Injection Ports:
M Controller/4 Signals
MP Controller/7 Signals
- Flexible Water Level Settings
- Easy-to-Use, 4-Compartment Dispenser
Allows for Convenient Manual Loading of
Detergent, Bleach and Fabric Softener
- Ergonomic, Easy-Grip Handle
- 5/3-Year Limited Warranty

EcoWash 200G Rigid-Mount Washers

Rapid-Spin Model Numbers

EWR-25
EWR-30
EWR-40
EWR-60



Rigid-Mount

EcoWash rapid-spin washer/extractors (200Gs) are constructed with structural tube design frame to help provide superior strength and optimal stability.

Durable Door Lock and Handle

The durable, ergonomic design of the door handle combined with our Easy Lock door lock provides maximum convenience.

5/3-Year Limited Warranty

ADC's EcoWash machines carry a 5/3-year limited warranty.

Intuitive Micro Controls (IMC)

Programmable microprocessor controls that are customizable and easy-to-use.

M Controller (Standard)

- 10 cycle options
- Selectable water levels
- Selectable wash temperatures
- Modify cycle times in wash, rinse and spin phase
- Rapid cycle advance
- Simple diagnostic control



MP Controller (Optional)

- 99 cycle options
- 16 standard cycles
- 83 programmable cycles
- Fully programmable cycles with computer software-enabled setup capabilities
- Rapid cycle advance
- Simple diagnostic control



	EWR-25 (200 G-FORCE)	EWR-30 (200 G-FORCE)	EWR-40 (200 G-FORCE)	EWR-60 (200 G-FORCE)
DRUM				
Load Capacity (lb/kg)	25 / 11.3	30 / 13.60	40 / 18.14	60 / 25
Drum Volume (cu. ft./liter)	3.33 / 94	4.59 / 130	6.35 / 180	8.82 / 250
Drum Diameter (in/mm)	20.94 / 532	24.41 / 620	24.41 / 620	27.56 / 700
Drum Depth (in/mm)	16.73 / 425	16.93 / 430	22.83 / 580	26.38 / 670
DIMENSIONS				
Width (in/mm)	27.24 / 692	31.10 / 790	31.10 / 790	34.84 / 885
Depth (in/mm)*	31.12 / 790	34.25 / 890	37.75 / 959	44.37 / 1127
Height (in/mm)	45.67 / 1160	51.18 / 1300	51.18 / 1300	55.25 / 1403
Weight (lb/kg)	458 / 208	496 / 225	542 / 246	705 / 320
DIMENSIONS WITH PACKAGING				
Crated Width (in/mm)	29.12 / 739	32.5 / 826	32.5 / 826	36.50 / 927
Crated Depth (in/mm)	38.12 / 968	39.00 / 991	45.00 / 1143	49.00 / 1245
Crated Height (in/mm)	53.75 / 1365	60.25 / 1530	61.25 / 1556	64.50 / 1638
Crated Weight (lb/kg)	488 / 221	536 / 243	592 / 269	765 / 347
DOOR				
Height to Bottom of Door	16.06 / 408	16.81 / 427	16.31 / 427	18.66 / 474
Door Opening Diameter (in/mm)	11.41 / 290	14.70 / 373	14.70 / 373	14.70 / 373
POWER				
Voltage/Phase (50hz or 60hz)	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH
Full Load Current / Breaker (amps)—1PH	5.26 / 15	6.35 / 15	11.56 / 15	13.00 / 20
Full Load Current / Breaker (amps)—3PH	3.88 / 15	4.51 / 15	7.53 / 15	9.54 / 15
CONNECTIONS				
Water Inlet (GHT/BSP)	¾" / ¾"	¾" / ¾"	¾" / ¾"	¾" / ¾"
Steam Inlet (BSP)	½"	½"	½"	¾"
Drain (in/mm)	3 / 76.2	3 / 76.2	3 / 76.2	3 / 76.2
CYLINDER SPEED				
Washing Speed (rpm)	50	50	50	47
Spinning Speed (rpm)	820	760	760	715
G-Force	200	200	200	200
WATER				
Average Usage (gallons)**	22.18	27.52	40.56	49.71

*Depth measured from the front panel to the furthest extent of the back guard, EWR-30, 40 and 60 have a 2-¾" deep bubble on the back that is included in the depth dimension.

**One wash, two rinse cycles.

Three-Year Limited Warranty on Parts.

For the first three (3) years from the date of purchase, when this commercial appliance is installed, maintained and operated according to the instructions attached to or furnished with the product, American Dryer brand of Whirlpool Corporation (hereafter "ADC") will pay for factory-specified parts or original equipment manufacturer parts to correct defects in materials or workmanship.

Fourth- and Fifth-Year Limited Warranty on Certain Parts.

In the fourth and fifth years from the date of purchase, ADC will pay for the following washer parts: the outer shell, drum and shaft assembly, inner welded frame, and bearings and seals.